

IN THE CLAIMS

14. (Original) A remotely controllable transfer switch comprising:
a circuit breaker housing;
a first line terminal;
a second line terminal;
a load terminal;
separable contacts electrically connected to said first line terminal;
a transfer arm electrically connected to said load terminal and adapted to pivot between a first position in which said transfer arm is electrically connected to said separable contacts and a second position in which said transfer arm is electrically connected to said second line terminal;
a solenoid having a first coil, a second coil and a plunger engaging said transfer arm;
a control circuit for said solenoid including a first terminal adapted to receive a first external signal, a second terminal adapted to receive a second external signal, and a third terminal adapted to receive a control voltage, said control circuit responsive to said first external signal to energize said first coil with said control voltage in order to move said plunger in a first direction to pivot said transfer arm to the first position thereof, said control circuit responsive to said second external signal to energize said second coil with said control voltage in order to move said plunger in a second direction to pivot said transfer arm to the second position thereof; and
an operating mechanism for opening and closing said separable contacts.

15. (Original) The transfer switch of Claim 14 wherein said operating mechanism includes an auxiliary contact having a first state when said separable contacts are open and a second state when said separable contacts are closed; and wherein said control circuit includes means for inputting said auxiliary contact and moving said transfer arm to the first position thereof in response to the first state of said auxiliary contact.

16. (Original) The transfer switch of Claim 14 wherein said control circuit further includes a micro-switch having a normally open contact electrically connected in series with the first coil, a normally closed contact electrically connected in series with the second coil, and an operating member for switching said normally open contact and said normally closed contact, said normally closed contact and said normally open contact having a common terminal electrically connected to said third terminal to receive said control voltage

to energize one of the first and second coils; and wherein the plunger of said solenoid has a projection which engages and actuates the operating member in the first position of said transfer arm, thereby causing said normally closed contact to open and said normally open contact to close.

17. (Original) The transfer switch of Claim 14 wherein said housing includes a pivot point; and wherein said transfer arm includes a first end, a second end and a pivot therebetween, said pivot pivotally engaging the pivot point of said housing, in order to pivot said transfer arm between the first and second positions thereof.


18. (Original) The transfer switch of Claim 17 wherein the plunger of said solenoid engages the transfer arm between the pivot and one of the first and second ends thereof.

19. (Original) The transfer switch of Claim 14 wherein said housing includes a pivot point; wherein said separable contacts are electrically connected with a conductor; and wherein said transfer arm includes a first end, a second end and an intermediate portion therebetween, the first end having a pivot adapted for movement of the transfer arm between the first and second positions thereof, the second end having a first contact adapted for electrical connection with the conductor of said separable contacts in the first position of said transfer arm and a second contact adapted for electrical connection with the second line terminal in the second position of said transfer arm, the plunger of said solenoid moving the intermediate portion of said transfer arm.

20. (Original) The transfer switch of Claim 19 wherein the plunger of said solenoid engages the transfer arm at the intermediate portion thereof.

21. (Original) The transfer switch of Claim 14 wherein the control voltage has a return; wherein the first terminal is adapted for electrical connection with a first remote contact which is referenced to the return of the control voltage; and wherein the second terminal is adapted for electrical connection with a second remote contact which is referenced to the return of the control voltage.

Respectfully submitted,

A handwritten signature in dark ink, appearing to read 'M. J. Moran', with a long horizontal flourish extending to the right.

Attorney for Applicant(s)

Tele: 412-787-6473

Fax : 412-494-3387

M. J. Moran
Reg. N. 26,694